



# 018F6857 🗷

# Solenoid coil, BG024DS

 $Product\ name: Solenoid\ coil, Type: BG024DS, Coil\ connection: Connection\ box$ 

## **PRODUCT DETAILS**

I NODUCI DEIAIES	
Gross weight	0.6 kg
Net weight	0.57 kg
EAN	5702428026260
Actuator size	13.5 mm
Ambient temperature range [°C]	50 °C
[Max]	
Ambient temperature range [°C]	-40 °C
[Min]	
Ambient temperature range [°F]	120 °F
[Max]	
Ambient temperature range [°F]	-40 °F
[Min]	
Approval	LLC CDC TYSK
	CE
	CMIM
	EAC
	UKCA
Coil connection	Connection box
Coil design standard	VDE 0580
Coil fastening	Clip-on
Coil type	1
Coil winding insulation class	Class H to IEC 85
Colour	Blue
Compliance	EN 60730-1
Duty rating	Continuous
Electrical connection	Terminal box
Electrical connection size	Pg 13.5
Electrical connector	Screwed cable entry
Enclosure rating IP	IP67
Packing format	Multi pack
Parts Program name	EV210B
	EV212B
	EV220B 15 - 50
	EV220B 6 - 22
	EV220B 65 - 100
	EV222B
	EV224B
	EV250B
Power consumption [W] DC	16 W



#### **PRODUCT DETAILS**

Solenoid coil accessories	
Solenoid valves	
Solenoid coil	
24 pc	
Lead (CAS no. 7439-92-1)	
100 %	
0 %	
No	
018F6857	
24 V	
BG024DS	
BG024DS	
	Solenoid valves Solenoid coil 24 pc Lead (CAS no. 7439-92-1)  100 % 0 % No 018F6857 24 V BG024DS

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store 🖸

#### **Accessories**



## 042N1256 12

**Accessory Cable Plug IP67, EN175301-803**Type: SPARE PART, Type designation: Cable plug

## **Spare Parts**



## 016D3331 🗷

Solenoid valve, EV220B, Flange, 3 in, NBR, NC

Body material: Cast iron, Operation: Servo-operated (piston), Number of ways: 2/2



## 032U3621 <sup>12</sup>

Solenoid valve, EV210B, Function: NC, G, 3/4, EPDM

Body material: DZR brass, Operation: Direct-operated, Number of ways: 2/2



### 032U8365 @

Solenoid valve, EV224B, Function: NO, G, 1, NBR

Approval: DNVGL-CG-0339, Body material: Brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2

#### For more information, please use this link to visit the product page on Danfoss Product Store 🗷



#### **Spare Parts**



#### 032U8509 🗷

#### Solenoid valve, EV220B, G, 1 1/4, FKM, NC

Approval: CE; PED, Body material: Stainless steel, Operation: Servo-operated (diaphragm), Number of ways: 2/2



#### 032H8041 🗷

#### Solenoid valve, EV210A, Function: NC, G, 1/4, FKM

Body material: Stainless steel, Operation: Direct-operated, Number of ways: 2/2



## 032U8511 🗈

## Solenoid valve, EV220B, G, 2, FKM, NC

Approval: CE; PED, Body material: Stainless steel, Operation: Servo-operated (diaphragm), Number of ways: 2/2



#### 032U5702 🗷

#### Solenoid valve, EV210B, Function: NC, G, 1/8, FKM

Approval: DNVGL-CG-0339, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2



#### 032U7173 🗷

#### Solenoid valve, EV220B, G, 1 1/4, NBR, NC

Approval: CE; DNVGL-CG-0339, Body material: Brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2



## 032U7172 🗷

# Solenoid valve, EV220B, G, 1, NBR, NC

Approval: DNVGL-CG-0339, Body material: Brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2



#### 032U8502 🗷

### Solenoid valve, EV220B, G, 1, EPDM, NC

Approval: ACS; PZH, Body material: Stainless steel, Operation: Servo-operated (diaphragm), Number of ways: 2/2



### 016D3330 @

# Solenoid valve, EV220B, Flange, 2 1/2 in, NBR, NC

Body material: Cast iron, Operation: Servo-operated (piston), Number of ways: 2/2



#### 032U3623 🗷

## Solenoid valve, EV210B, Function: NC, G, 1, EPDM

Body material: DZR brass, Operation: Direct-operated, Number of ways: 2/2

#### For more information, please use this link to visit the product page on Danfoss Product Store 🗷



#### **Spare Parts**



#### 032U7180 🗷

#### Solenoid valve, EV220B, G, 1/2, NBR, NO

Approval: DNVGL-CG-0339; EAC; LLC CDC EURO-TYSK; UL, Body material: Brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2



#### 032U8500 🗷

#### Solenoid valve, EV220B, G, 1/2, EPDM, NC

Approval: ACS; PZH, Body material: Stainless steel, Operation: Servo-operated (diaphragm), Number of ways: 2/2



#### 032U8505 🗷

#### Solenoid valve, EV220B, G, 2, EPDM, NC

Approval: ACS; CE; PZH, Body material: Stainless steel, Operation: Servo-operated (diaphragm), Number of ways: 2/2



#### 032U8506 12

## Solenoid valve, EV220B, G, 1/2, FKM, NC

Approval: DNV; EAC; UL, Body material: Stainless steel, Operation: Servo-operated (diaphragm), Number of ways: 2/2



#### 032U1200 @

# Solenoid valve, EV210B, Function: NC, G, 1/8, NBR

Approval: DNVGL-CG-0339; GL, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2



## 032U7175 <sup>™</sup>

#### Solenoid valve, EV220B, G, 2, NBR, NC

Approval: CE; DNVGL-CG-0339, Body material: Brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2



## 032U5709 12

## Solenoid valve, EV210B, Function: NC, G, 1/4, EPDM

Approval: ACS; DNVGL-CG-0339; GL; PZH, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2



#### 032U8361 <sup>12</sup>

### Solenoid valve, EV224B, Function: NO, G, 1/2, NBR

Approval: DNVGL-CG-0339, Body material: Brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2



### 032U8503 🗷

## Solenoid valve, EV220B, G, 1 1/4, EPDM, NC

Approval: ACS; CE; PZH, Body material: Stainless steel, Operation: Servo-operated (diaphragm), Number of ways: 2/2

#### For more information, please use this link to visit the product page on Danfoss Product Store



#### **Spare Parts**



## 032U3605 🗷

#### Solenoid valve, EV210B, Function: NC, G, 3/8, EPDM

Approval: ACS, Body material: Brass, Operation: Direct-operated, Number of ways: 2/2



## 032U7170 🗷

#### Solenoid valve, EV220B, G, 1/2, NBR, NC

Approval: DNVGL-CG-0339, Body material: Brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2



## 032U8360 🗷

## Solenoid valve, EV224B, Function: NC, G, 1/2, NBR

Approval: DNVGL-CG-0339, Body material: Brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2



## 032U3601 🗷

#### Solenoid valve, EV210B, Function: NC, G, 1/4, FKM

Body material: Brass, Operation: Direct-operated, Number of ways: 2/2



## 032U8364 <sup>12</sup>

#### Solenoid valve, EV224B, Function: NC, G, 1, NBR

Approval: DNVGL-CG-0339, Body material: Brass, Operation: Servo-operated (diaphragm), Number of ways: 2/2