

**032F1204****Solenoid valve, EVR 3, NC**

Cv value [gal/min]: 0.310, Manual operation option: No, Packing format: Multi pack

**PRODUCT DETAILS**

<b>Gross weight</b>	0.25 kg
<b>Net weight</b>	0.17 kg
<b>EAN</b>	5702422004189
<b>Actuator system [mm]</b>	13.5 mm
<b>Ambient temperature</b>	-40 - 80 °C
<b>Ambient temperature range [°F]</b> [Max]	175 °F
<b>Ambient temperature range [°F]</b> [Min]	-40 °F
<b>Approval</b>	EAC LLC CDC TYSK
<b>Category</b>	Art. 4, par. 3
<b>Coil</b>	No
<b>Cv value [gal/min]</b>	0.31 gal/min
<b>Direction</b>	Straightway
<b>Fluid Group</b>	1;2
<b>Function</b>	NC
<b>Identical product</b>	032F5084
<b>Inlet connection type</b>	Solder, ODF
<b>Inlet size [in]</b>	3/8 in
<b>Kv value [m<sup>3</sup>/h]</b>	0.27 m <sup>3</sup> /h
<b>Manual operation option</b>	No
<b>Max. Working Pressure [bar]</b>	45.2 bar
<b>Max. Working Pressure [psig]</b>	655 psig
<b>MaxOPD[bar] 10W AC</b>	38 bar
<b>MaxOPD[psi] 10W AC</b>	550 psi
<b>Medium temp. range note</b>	Defrost max 130°C/265°F
<b>Medium temperature range [°C]</b> [Max]	105 °C
<b>Medium temperature range [°C]</b> [Min]	-40 °C
<b>Medium temperature range [°F]</b> [Max]	221 °F
<b>Medium temperature range [°F]</b> [Min]	-40 °F
<b>MinODP [bar]</b>	0 bar
<b>MOPD[bar/psi]</b>	COIL DEPENDENT
<b>MWP [bar] PED compliant</b>	49 bar
<b>Orifice size [mm]</b>	3.3 mm

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

**Product Detail | Solenoid valve, EVR 3, NC**
**PRODUCT DETAILS**

<b>Outlet connection type</b>	Solder, ODF
<b>Outlet size [in]</b>	3/8 in
<b>Packing format</b>	Multi pack
<b>Parts Program name</b>	EVR
<b>Product accessories</b>	Solenoid valve accessories
<b>Product family name</b>	EVR
<b>Product group</b>	Solenoid valves
<b>Product name</b>	Solenoid valve
<b>Quantity per packing format</b>	24 pc
<b>REACH Candidate List substances</b>	Lead (CAS no. 7439-92-1)
<b>&gt;0.1%</b>	
<b>Refrigerants</b>	R1234yf R125 R134a R152a R22 R290 R32 R404A R407A R407C R407F R410A R417A R448A R449A R450A R452A R600 R600a R513A R452B R454B R1234ze(E) R407H R413A R422A R422B R422D R438A R442A R444B R447A R447B R449B R454C R455A R463A R512A R513B R515A R515B R516A R454A

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

**Product Detail | Solenoid valve, EVR 3, NC**

---

**PRODUCT DETAILS**

---

	R507A
<b>Serviceable</b>	Solenoid valve spare parts
<b>Type</b>	EVR 3
<b>Type designation</b>	Solenoid valve, Solder
<b>Valve operation</b>	Direct
<b>Proposition 65</b>	WARNING: Cancer and Reproductive Harm <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>

---

**For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)**