



## 032L8101 🗷

# Solenoid valve, EVR 15, NC

Cv value [gal/min]: 3.470, Manual operation option: No, Packing format: Multi pack

## **PRODUCT DETAILS**

Gross weight	0.91 kg
Net weight	0.67 kg
EAN	5702428952484
Actuator system [mm]	13.5 mm
Ambient temperature	-40 - 80 °C
Approval	UL
	EAC
	LLC CDC EURO-TYSK
Category	Art. 4, par. 3
Coil	No
Cv value [gal/min]	3.47 gal/min
Direction	Straightway
Fluid Group	1;2
Function	NC
Inlet connection type	Flare
Inlet size [in]	5/8 in
Inlet size [mm]	16 mm
Kv value [m³/h]	2.97 m³/h
Manual operation option	No
Max. Working Pressure [bar]	45.2 bar
Max. Working Pressure [psig]	655 psig
MaxOPD[bar] 10W AC	38 bar
MaxOPD[bar] 20W DC	20 bar
MaxOPD[bar] coil BJ/BX	38 bar
MaxOPD[psi] 10W AC	550 psi
MaxOPD[psi] 20W DC	290 psi
MaxOPD[psi] coil BJ/BX	550 psi
Medium temperature range [°C]	105 ℃
[Max]	
Medium temperature range [°C]	-40 °C
[Min]	
Medium temperature range [°F]	221 °F
[Max]	
Medium temperature range [°F]	-40 °F
[Min]	
MinODP [bar]	0.03 bar
MinODP [psi]	0.44 psi
MOPD[bar/psi]	COIL DEPENDEND
Orifice size [mm]	14 mm

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.



### **PRODUCT DETAILS**

PRODUCT DETAILS		
Outlet connection type	Flare	
Outlet size [in]	5/8 in	
Outlet size [mm]	16 mm	
Packing format	Multi pack	
Parts Program name	EVR	
Product accessories	Solenoid valve accessories	
Product family name	EVR v2	
Product group	Solenoid valves	
Product name	Solenoid valve	
Quantity per packing format	12 pc	
REACH Candidate List substances	Lead (CAS no. 7439-92-1)	
>0.1%	,	
Refrigerants	R125	
· ·	R134a	
	R404A	
	R407A	
	R407F	
	R410A	
	R417A	
	R448A	
	R449A	
	R450A	
	R452A	
	R513A	
	R407H	
	R413A	
	R422A	
	R422B	
	R422D	
	R438A	
	R447A	
	R449B	
	R463A	
	R513B	
	R515A	
	R515B	
	R442A	
	R447B	
	R512A	
	R22	
	R407C	
	R455A	
	R1234yf	
	R1234ze(E)	
	R152a	
	R32	
	R444B	
	R452B	
	R454A	
	R454B	
	R454C	
	R507A	
	R516A	
Serviceable	Solenoid valve spare parts	

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.



## **PRODUCT DETAILS**

Туре	EVR 15
Type designation	Solenoid valve
UL approved refrigerants	R125
	R134a
	R22
	R404A
	R407A
	R407C
	R407F
	R407H
	R410A
	R413A
	R417A
	R422A
	R422B
	R422D
	R438A
	R442A
	R447A
	R447B
	R448A
	R449A
	R449B
	R450A
	R452A
	R463A
	R507A
	R512A
	R513A
	R513B
	R515A
	R515B
Valve operation	SERVO-DIAPHRAGM
Proposition 65	WARNING: Cancer and Reproductive
	Harm
	www.p65warnings.ca.gov

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store 🗷