



067N2008 🗷

Thermostatic expansion valve, TGE, R22/R407C

Temperature range [°F]: -15 - 50, MOP Point [°F]: 60, Orifice capacities [kW]: 38.00, Orifice capacities [TR]: 11.00, Pressure equalization: Externally equalized, Superheat setting: Adjustable

PRODUCT DETAILS

PRODUCT DETAILS	
Gross weight	0.49 kg
Net weight	0.39 kg
EAN	5702428138635
Approval	C UL US LISTED
	EAC
	LLC CDC TYSK
Balanced port [Yes/No]	Yes
Body material	Brass
Bulb temperature max. [°C]	150 °C
Bulb temperature max. [°F]	302 °F
Capillary tube length [in]	59 in
Capillary tube length [mm]	1500 mm
Connection material	Copper
Direction	Straightway
Element temperature max. [°C]	110℃
Element temperature max. [°F]	230 °F
Equalization connection type	Solder, ODF
Equalization size [in]	1/4 IN
Flow direction	Bi-flow
Flow direction indicator	Embossed 1-way arrow
Identical product	067N2028
Inlet connection type	Solder, ODF
Inlet size [in]	5/8 in
Max. Working Pressure [bar]	49 bar
Max. Working Pressure [psig]	711 psig
MOP Point [psig]	MOP 100
MOP Point [°C]	15 ℃
MOP Point [°F]	60 °F
Orifice capacities [kW]	38 kW
Orifice capacities [TR]	11 tons
Orifice size	11
Outlet connection type	Solder, ODF
Outlet size [in]	1 1/8 in
Packing format	Multi pack
Parts included	Bulb strap
Pressure equalization	Externally equalized
Product accessories	TXV accessories
Product description	Thermostatic Expans. Valve

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.



PRODUCT DETAILS

Product family name	TGE
Product group	Expansion valves
Product name	Thermostatic expansion valve
Quantity per packing format	12 pc
Rated cap. cond. Range N [IMP]	tcond=100 °F
	tevap=40 °F
	tliq=98 °F
Rated cap. cond. Range N [SI]	tcond=38 °C
	tevap=4.4 °C
	tliq=37 °C
REACH Candidate List substances	Lead (CAS no. 7439-92-1)
>0.1%	
Refrigerants	R22/R407C
Serviceable	No
Static Superheat (SS) [°C]	4°C
Static Superheat (SS) [°F]	7.2 °F
Superheat setting	Adjustable
Temperature range [°C] [Max]	10 ℃
Temperature range [°C] [Min]	-25 °C
Temperature range [°F] [Max]	50 °F
Temperature range [°F] [Min]	-15 °F
Туре	TGE
UL approved refrigerants	R22
	R407C
Valve body temp. max. [°C]	150 °C
Valve body temp. max. [°F]	302 °F
Proposition 65	WARNING: Cancer and Reproductive
	Harm
	www.p65warnings.ca.gov

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store 🖸

Accessories



067N0557 🗷

Generic accessories, Spare Part Bulb Strap L225mm I/40 Spare Part Bulb Strap L225mm I/40, Used for product: TE; TGE

068U3506 🗷



TXV accessories, Accessory 0.4mm bulb strap I/45

Accessory 0.4mm bulb strap I/45, Used for product: T 2; TE 2; TR 6; TU

For more information, please use this link to visit the product page on Danfoss Product Store 🗅

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.



Accessories



068U3508 🗷

TXV accessories, Accessory bag with long Bulb strap M/45

Accessory bag with long Bulb strap M/45, Used for product: T 2; TC; TE 2; TU