

Qty. Description

1 UPS 26-99 FC



Note! Product picture may differ from actual product

Product No.: [52722513](#)

The pump is of the canned rotor type, i.e. pump and motor form an integral unit without shaft seal and with only two gaskets for sealing.

The bearings are lubricated by the pumped liquid.

The pump has 3-step speed selector.

The pump is characterized by:

- * Ceramic shaft and radial bearings.
- * Carbon axial bearing.
- * Stainless steel rotor can and bearing plate.
- * Corrosion-resistant impeller, Composite.
- * Cast iron pump housing.

The motor is a 1-phase motor.

No additional motor protection is required.

Liquid:

Pumped liquid: Water
 Liquid temperature range: 2 .. 110 °C
 Selected liquid temperature: 60 °C
 Density: 983.2 kg/m³

Technical:

Rated flow: 4.02 m³/h
 Max flow: 7.5 m³/h
 Rated head: 5.018 m
 Approvals: CUL

Materials:

Pump housing: Cast iron
 EN 1561 EN-GJL-200
 ASTM A48-30B
 Impeller: Composite
 PES+30% GF

Installation:

Max. ambient: 40 °C
 Amb. max at 80 dgr C liquid: 80 °C
 Maximum operating pressure: 10 bar
 Type of connection: OVAL
 Pipe connection: 2-BOLT FLANGE
 Pressure rating for connection: PN 10
 Port-to-port length: 165 mm

Electrical data:

Power input in speed 1: 150 W



Company name:

Created by:

Phone:

Date:

22/03/2023

Qty.	Description
------	-------------

1	Power input in speed 2: 179 W
	Max. power input: 196 W
	Mains frequency: 60 Hz
	Rated voltage: 1 x 230 V
	Current in speed 1: 0.7 A
	Current in speed 2: 0.8 A
	Current in speed 3: 0.9 A
	Capacitor size - run: 5 μ F/400 V
	Number of poles: 2
	Insulation class (IEC 85): F
	Built-in motor protection: CONTACT
	Others:
	Terminal box position: 9H o'clock
	Net weight: 4.3 kg
	Gross weight: 4.64 kg