



QUALITY EQUIPMENT CORP.

MIAMI, FLORIDA


Rubber Insulation Sheet

Made of the same material as SCflex pipe, it's widely used for insulating pipe and duct, helping stopping condensation and energy-saving. Meanwhile, it's also selected to be made to various shapes for thermal insulation, gasket, noise-reduction vibration-dampening uses.

Standard Size

TK: 3mm; 6mm; 9mm; 13mm; 16mm; 19mm; 25mm

Width: 1m; Length: 1.2m; 10m



Technical Data

DENSITY (KG/M ³)	70-90
THERMAL CONDUCTIVITY (W/(M.K))	-20°C 0°C 40°C
TEMPERATURE RANGE	0.031 0.034 0.038
WATER VAPOUR PERMEABILITY	-50°C to +110°C (Flat surfaces + 85°C)
WATER ABSORPTION (%by weight)	μ>4500
OZONE RESISTANCE	<5%
FIRE RATING	Excellent
COMPRESSION SET	GB 8624B1 (OXYGEN INDEX >34%)
TEARS STRENGTH	self-extinguishing
	non-flammable
	70%
	74N/cm

Aluminum / Polyester Foil Combined Insulation

Made of insulation roll with aluminum / polyester foil, aluminum / polyester foil combined insulation provide perfect properties for avoid of vapor penetration and excellent reflection.

TK:3mm,6mm,9mm,13mm,16mm,19mm,25mm

Width:1mm

length: 1.2m,10m



Construction

		Metalized	Metalized	
Foil Backing	PET+Aluminum	Polyester	Polyester with Scrim	None
Adhesive System	Acrylic/Rubber	Acrylic/Rubber	Acrylic/Rubber	Acrylic/Rubber
Liner	Kraft/PE	Kraft/PE	Kraft/PE	Kraft/PE