

ZP137KCE-TF5

HFC, R-410A, 60Hz, 3- Phase, 200/230 V

Air Conditioning



Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

<u>Evap(°F)/Cond(°F)</u>	<u>45 / 130</u>	<u>45 / 100</u>
<u>RG(°F)/Liq(°F)</u>	<u>65 / 115</u>	<u>65 / 85</u>
Capacity (Btu/hr)	137000	168000
Power (Watts):	12400	8750
Current (Amps):	38.00	29.70
EER (Btu/Wh):	11.00	19.20
Mass Flow (lbs/hr):	2020	2080
Sound Power (dBA):	80 Avg	85 Max
Vibration (mils(peak- Record Date:	3.0 Avg 2005-07-15	4.5 Max

Mechanical

Number of Cylinders:	0	Displ(in ³ /Rev):	7.76
Bore Size(in):	0.00	Displ(ft ³ /hr):	942.81
Stroke(in):	0.00		
Overall Length (in):	10.38	Mounting Length (in):	7.50
Overall Width (in):	11.23	Mounting Width (in):	7.50
Overall Height (in):	21.00	Mounting Height (in):	21.75 *
Suction Size (in):		1 3/8 Stub	
Discharge Size (in):		7/8 Stub	
Oil Recharge (oz):		106	
Initial Oil Charge (oz):		110	
Net Weight (lbs):		138	
Internal Free Volume (in ³):			
Horse Power:			
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

Electrical

LRA-High*:	245.0	MCC (Amps):	75.0	UL File No:	SA-2337
LRA-Half Winding:		RPM:		UL File Date:	27-Sep-1996
LRA Low*:		Max Operating Current:	55.0		
RLA(=MCC/1.4;use for contactor selection):			53.6		
RLA(=MCC/1.56;use for breaker & wire size)			48.1		
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

Alternate Applications

<u>Refrigerant</u>	<u>Freq (Hz)</u>	<u>Phase</u>	<u>Voltage</u>	<u>Application</u>
R-410A HFC	50	3	200/220	Air Conditioning